## PH305 - SEWER JET - 2800 PSI

## Polyhose Proprietary Product

Construction

Core Thermoplastic Elastomer

Reinforcement One Braid of Synthetic Fiber and one special braid of synthetic fiber armoring

Cover Polyurethane, Yellow Colour

Application Ideal for those tough jobs with tight bends. Abrasion and cut resistant cover. Bonded construction to resist kinking.

Design includes "armoring", enhancing flexibility and wear life. Cover material specially compounded to resist

microbiological degradation. Available in long lengths

Note: Special colours available on request

| Item Code | Dash<br>Size | DN |      |      | OD OD |      | AM (C) |     | BP (B) |     | BR/r |     | <b>⊗</b><br>⊗ |
|-----------|--------------|----|------|------|-------|------|--------|-----|--------|-----|------|-----|---------------|
|           | Size         |    | inch | mm   | inch  | mm   | psi    | bar | psi    | bar | inch | mm  | g/m           |
| PH305-08  | -08          | 12 | 1/2  | 12.7 | 0.805 | 20.4 | 2,800  | 190 | 6,900  | 475 | 4.0  | 100 | 277.0         |
| PH305-12  | -12          | 20 | 3/4  | 19.0 | 1.160 | 29.5 | 2,800  | 190 | 6,900  | 475 | 4.7  | 120 | 495.0         |
| PH305-16  | -16          | 25 | 1    | 25.4 | 1.460 | 37.1 | 2,800  | 190 | 6,900  | 475 | 6.0  | 150 | 717.0         |



Temperature Range: Continuous: -40°C to +60°C