

PH 626 - DRY CEMENT DELIVERY / SILO HOSE

Polyhose Proprietary Product

Construction

- Core** Black colour, Synthetic and natural rubber blend resistant to abrasion
- Reinforcement** Synthetic textile cord yarn fabric with antistatic copper wire
- Cover** Black colour, Synthetic rubber resistant to ozone, weather and abrasion
- Application** For transfer of Dry Cement, Sand, Crusher Dust from Silo/ Tanker



Item Code	Dash Size	ID		OD		WP		BP		W
		inch	mm	inch	mm	psi	bar	psi	bar	kg/m
PH626-16	-16	1	25.0	1.46	37.0	150	10	450	30	0.83
PH626-20	-20	1.1/4	32.0	1.73	44.0	150	10	450	30	1.01
PH626-24	-24	1.1/2	38.0	1.97	50.0	150	10	450	30	1.30
PH626-32	-32	2	51.0	2.56	65.0	150	10	450	30	1.70
PH626-40	-40	2.1/2	64.0	3.07	78.0	150	10	450	30	2.10
PH626-48	-48	3	76.0	3.54	90.0	150	10	450	30	2.70
PH626-64	-64	4	102.0	4.65	118.0	150	10	450	30	4.40
PH626-80	-80	5	127.0	5.79	147.0	150	10	450	30	5.70
PH626-96	-96	6	152.0	6.77	172.0	150	10	450	30	7.00
PH626-128	-128	8	203.0	8.94	227.0	150	10	450	30	9.00



Temperature Range: Continuous: -30°C to +70°C