

PH365 - AIR / WATER HOSE

Applicable Standard: Polyhose proprietary product Exceeds IS 446-1980 - Type 3 & IS 446-1980-Type 1



Construction

Core Plasticized PVC, Black

Reinforcement Single braid of Synthetic fiber

Cover Abrasion resistant thermo-compound, black Colour

Application Specially designed for Tyre inflation, light engineering industry and general purpose air line

Note: Special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH365-04	-04	06	1/4	6.5	0.492	12.5	230	16	920	64	2.0	50	125.0
PH365-05	-05	08	5/16	8.0	0.571	14.5	230	16	920	64	3.0	75	155.0
PH365-06	-06	10	3/8	9.5	0.630	16.0	230	16	920	64	4.0	100	180.0
PH365-08	-08	12	1/2	12.7	0.795	20.2	230	16	920	64	4.3	110	260.0
PH365-12	-12	19	3/4	19.0	1.067	27.1	145	10	580	40	5.0	125	400.0
PH365-16	-16	25	1	25.4	1.299	33.0	145	10	580	40	6.0	150	500.0



Temperature Range: Continuous: -10°C to +60°C