PH358 - R7 COMPACT HOSE

Polyhose Proprietary Product

Construction

Core Polyamide (Composite tube)

Reinforcement One or more Braids of Synthetic Fiber

Cover Polyurethane, Black Colour, Pin pricked

Application Medium Pressure Hydraulic Lines 70 to 210 bar. Suitable for hydraulic application with increased resistance to abrasion for use

with petroleum, synthetic or water based fluids in Hydraulic systems. Suitable for Agricultural machinery, Earthmoving,

Articulating & Telescopic booms and Material handling equipments

Note: Available Twin & Multi lines with different Hose combination and size. Also special colours available on request

Item Code	Dash Size	DN	ID ID		OD O		@ WP		Ø. BP		BR/r		₹
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	g/m
PH358-03	-03	05	3/16	4.8	0.409	10.4	3,000	210	12,000	840	8.0	20	80.0
PH358-04	-04	06	1/4	6.4	0.500	12.7	2,800	195	11,200	780	1.0	25	120.0
PH358-06	-06	10	3/8	9.5	0.645	16.4	2,300	160	9,200	640	1.8	45	170.0
PH358-08	-08	12	1/2	12.7	0.805	20.4	2,000	140	8,000	560	2.6	65	250.0



Temperature Range: Continuous: -40°C to +100°C

Temp. not to exceed +70°C for Air and Water based fluids